


# commBOX Interactive Classic 55 V3 Specs



Classic 55  
CBIC55

SKU	Classic 55 CBIC55
Resolution	UD 3840x2160 @60Hz
Brightness	350cd/m <sup>2</sup>
Contrast Ratio	1300:1
Response Time	6ms
Viewing Angle	178°
Operating Con	0C to 40C
Operating Humidity	20-80%
Power Req	AC 100 to 240V, 50/60Hz
Power Consumption	140 W
Standby Consumption	<0.5 W
Touch	20 Points, 1mm
Touch Technology	Infra Red
VESA	400 x 400, M6
Android	8.0, 3GB RAM, 16GB Storage
Speakers	2 x 15W / 8Ω
Input/Output	3 x 2.0 HDMI in (ARC & CEC), Display Port in, VGA in, AV in, Component in, OPS in, LAN in, LAN out, WiFi, 4 x USB A in, 2 x USB Touch in, PC Audio in, RS232 in, HDMI out, AV out, Optical out, Audio out



Screen Dims	1298.4 (W) x 811.37 (H) x 117.07 (D)mm
Screen Weight	34.5 kg
Packed Dims	1420 (W) x 910 (H) x 245 (D)mm
Packed Weight	42 kg
Accessories	Remote (w\Batteries), 2 x stylus, power cord, USB touch cable, HDMI cable & wall bracket
Warranty	3 Year Onsite (Optional 4 or 5 Year)